BUY ONLINE FREE CATALOG SAVE UP TO 25%

SAFETY DATA SHEET

Synthetic Air Tool Oil

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification

Product identifier

Product name Synthetic Air Tool Oil

Product number AIR

Recommended use of the chemical and restrictions on use

Application Lubricating oil.

Uses advised against Avoid the formation of mists.

Details of the supplier of the safety data sheet

Supplier
AMSOIL INC.
Bordner, Ladner, Gervais
Scotia Plaza, 40 King St W
Toronto, ON, Canada M5H 3Y4
T: +1 416-367-6547

Manufacturer
AMSOIL INC.
One AMSOIL Center,
Superior, WI 54880, USA.
T: +1 715-392-7101

Emergency telephone number

Emergency telephone
CHEMTREC: Within USA and Canada: 1-800-424-9300
Outside the USA and Canada: +1 703-741-5970
(collect calls accepted) 24/7

2. Hazard(s) identification

Classification of the substance or mixture

OSHA/WHMIS Regulatory Status This Product is not Hazardous under the OSHA Hazard Communication Standard and according to the hazard criteria of the Hazardous Product Regulations.

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Label elements

Hazard statements NC Not Classified

Precautionary statements P102 Keep out of reach of children.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Hydrogenated base oil CAS number: 64742-54-7	**10 - <25%**
Classification Asp. Tox. 1 - H304	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Ingestion Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Skin Contact Wash with plenty of soap and water. Get medical attention if symptoms are severe or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 20 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact May cause temporary eye irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Contains Hydrocarbons. The product is immiscible with water and will spread on the water surface.
Hazardous combustion products	Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO2).

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Use protective equipment appropriate for surrounding materials.

Environmental precautions

Environmental precautions	Immiscible with water. Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous effects on the environment. Absorb spillage with non-combustible, absorbent material. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible. Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of contents/container in accordance with national regulations.
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not reuse empty containers. Avoid contact with used product.

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Under conditions which may generate mists, the following exposure limits are recommended:
Long-term exposure limit (8-hour TWA): 5 mg/m³
Short-term exposure limit (15-minute): 10 mg/m³

Ingredient comments The product contains no other substances classified as hazardous to health by an OEL value in concentrations which should be taken into account.

Exposure controls

Appropriate engineering controls Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Environmental exposure controls	Keep container tightly sealed when not in use.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Straw.
Odor	Mild hydrocarbon.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	250°C Cleveland open cup., [ASTM D92]
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.8478
Solubility(ies)	Not known.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	32.5 cSt @ 40°C 6.2 cSt @ 100°C [ASTM D 445]
Explosive properties	Not considered to be explosive.
Oxidizing properties	Does not meet the criteria for classification as oxidizing.
Fire point	270°C Cleveland open cup., [ASTM D92]
Pour point	-46°C [ASTM D 97]

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Toxicological effects	Not regarded as a health hazard under current legislation.

Acute toxicity - oral

Notes (oral LD_{50})	Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD_{50})	Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC_{50})	Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data	Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization	Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization	Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro	Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard	Based on available data the classification criteria are not met.

General information	No specific health hazards known. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin Contact	Prolonged contact may cause dryness of the skin.
Eye contact	May cause temporary eye irritation.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.

Toxicological information on ingredients.

Hydrogenated base oil

Acute toxicity - oral

Notes (oral LD_{50})	LD_{50} >5000 mg/kg, Oral, Rat REACH dossier information.

Acute toxicity - dermal

Notes (dermal LD_{50})	LD_{50} >5000 mg/kg, Dermal, Rabbit REACH dossier information.

Acute toxicity - inhalation

Notes (inhalation LC_{50})	LC_{50} >5.53 mg/l, Inhalation, Rat REACH dossier information.

Skin corrosion/irritation

Animal data	Dose: 0.5ml, 24 hours, Rabbit Erythema/eschar score: No erythema (0). Edema score: No oedema (0). REACH dossier information.

Serious eye damage/irritation

Serious eye damage/irritation	Dose: 0.1ml, 72 hours, Rabbit REACH dossier information.

Skin sensitization

Skin sensitization	Buehler test - Guinea pig: Not sensitizing. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity - fertility	Screening - NOAEL > 1000 mg/kg/day, Oral, Rat P REACH dossier information.
Reproductive toxicity - development	Developmental toxicity: - LOAEL: 125 mg/kg/day, Dermal, Rat REACH dossier information.

12. Ecological Information

Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
Toxicity	Based on available data the classification criteria are not met.

Ecological information on ingredients.

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Hydrogenated base oil

Acute aquatic toxicity

Acute toxicity - fish	LL_{50}, 96 hours: > 100 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EL_{50}, 48 hours: > 10000 mg/l, Daphnia magna
Acute toxicity - aquatic plants	NOEL, 72 hours: > 100 mg/l, Pseudokirchneriella subcapitata

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Hydrogenated base oil

Biodegradation	Water - Degradation 31: 28 days Inherently biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility The product is insoluble in water.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT, TDG).

UN Number

Not applicable.

UN proper shipping name

Not applicable.

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Transport hazard class(es)

Transport labels
No transport warning sign required.

Packing group

Not applicable.

Environmental hazards

Environmentally Hazardous Substance
No.

Special precautions for user

Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation (SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities
None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)
None of the ingredients are listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities
None of the ingredients are listed.

SARA 313 Emission Reporting
The following ingredients are listed:

Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)
1.0 %

CAA Accidental Release Prevention
None of the ingredients are listed.

SARA (311/312) Hazard Categories
None of the ingredients are listed.

OSHA Highly Hazardous Chemicals
None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins
None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-I)
The following ingredients are listed:

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

Triphenyl phosphite

California Air Toxics "Hot Spots" (A-II)
None of the ingredients are listed.

California Directors List of Hazardous Substances
None of the ingredients are listed.

Massachusetts "Right To Know" List
None of the ingredients are listed.

Rhode Island "Right To Know" List
None of the ingredients are listed.

Minnesota "Right To Know" List
None of the ingredients are listed.

New Jersey "Right To Know" List
None of the ingredients are listed.

Pennsylvania "Right To Know" List
None of the ingredients are listed.

Inventories

Canada - DSL/NDSL
All the ingredients are listed or exempt.

US - TSCA
All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification
None of the ingredients are listed or exempt.

16. Other information

Abbreviations and acronyms used in the safety data sheet	C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control Act; LD/LC/EC = Lethal Dose,Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE= Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very Bioaccumulative.
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision date	8/9/2017
Revision	0

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322

Synthetic Air Tool Oil

SDS No.	6048
Hazard statements in full	H304 May be fatal if swallowed and enters airways.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Order by Phone 1-800-956-5695 - Give Operator Reference #5983322